

ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.:+30 210 5557579, FAX: +30 210 5558482

THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.:+30 2310 467275, FAX: 2310 463442

## Neotextile

### Non-woven polyester reinforcement specially designed for waterproofing systems

#### Fields of application

- Suitable for reinforcement of coatings such as **Neorooft<sup>®</sup>**, **Silatex<sup>®</sup> Super**, **Neoproof<sup>®</sup> PU W**
- Specially recommended for covering cracks and upstands
- Compatible with any building surface, including metallic, for affixing.

#### Properties-Advantages

- Applied easily
- It does not torn
- It does not require great consumption of coatings for its impregnation
- It increases durability and efficiency of waterproofing systems

#### Technical characteristics

Consumption of reinforced coatings: 1, 5 kg/m<sup>2</sup>

Properties	Test Method	Mean Values
Weight	EN ISO 9864	50gr/m <sup>2</sup>
Thickness	EN ISO 9863/1	0,45mm
Tensile strength	EN ISO 10319	1,0 KN/m
Elongation at max. load	EN ISO 10319	≥ 50%

ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.:+30 210 5557579, FAX: +30 210 5558482

THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.:+30 2310 467275, FAX: 2310 463442

## Neotextile

---

**Instruction for use**

After the first layer of the coating is applied (the use of a primer is advisable for improving adhesion) place **Neotextile<sup>®</sup>**. At least two more coats are required for the complete coverage of the product.

---

**Storage stability**

Unlimited

---

**Packing**

Roll 300 x 1,08 m

Roll 100 x 1,08 m

Roll 50 x 1,08 m

Tape 10m x 9 cm

Tape 10m x 18 cm

---

